

## MaxxECU Plugin - Engine Specifics Audi A4 (AEB)

2016-01-28




Fig 1 - MaxxECU Plugin kit consist of the following parts:

1. MaxxECU CMC connector
2. Audi vehicle harness adapter.
3. 16-pin extra connector.
4. 3-pin connector for extra 0-5v sensor (ex. pressure sensor).

### ECU installation

- Stock Engine Control Unit (ECU) on this vehicle is mounted in engine bay on the left side.
- Disconnect the stock ECU from vehicle harness connector.
- Install MaxxECU harness into vehicle harness connector.
- Install included MAP-sensor into engine manifold with included hose kit.

## 16-pin connector




Fig 2 - Extra connector (3) seen from cable side.

1: Wideband.

2: Wideband.

3: Wideband.

4: Wideband.

5: GPO 5 (output)

6: GPO 7 (in / output)

7: DIN 2 (input)

8: GPO 4 (output)

9: Wideband.

10: Wideband.

11: Wideband.

12: +12V (output).

13: GND.

14: AIN 1

15: AIN 2 (input)

16: AIN 3 (0-5V) (input).

### Extra inputs.

GPO 7 (can be used as digital input), flexfuel sensor, switch.

DIN 2, flexfuel sensor, switch.

AIN 1, switch, temp.

AIN 3, 0-5V input.

AIN 4, 0-5V input. Extra 3-pin connector (4).




Fig 3 - 3-pin

Superseal connector.

1: Signal GND.

2: AIN 4 (0-5V) input.


3: +5V from ECU.

### Extra outputs.

Offers extra outputs for flexible control like boost control, fan control.

GPO 5, GPO 4, GPO 7(if not used as digital input) (GND switched outputs).

### Relay wirings



### Plugin Trigger

Using stock triggers on crank and cam.

### Notes

MaxxECU has some built in output test and diagnostics, see [Diagnostics -> Output test](#) to test certain outputs.

This will only work if fuel pump is set to "Always active" since fuel pump relay is also powering injectors and ignition.